



Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

Safety Data Sheet (DP218)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: HB42 Wood Filler

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance / the mixture: Wood Repair

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Hilton Banks Limited

74 Oldfield Road

Hampton

Middlesex TW12 2HR

Tel: 020 8979 8284

E-mail: enquiries@hiltonbanks.com

Internet: www.hiltonbanks.com

Further information obtainable from:

Product safety department.

enquiries@hiltonbanks.com

1.4 Emergency telephone number:

Tel: 020 8979 8284

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification under CLP: * Eye Irrit. 2: H319; Skin Irrit. 2: H315

Most Important adverse effect: Causes skin irritation. Causes serious eye irritation.





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

2.2 Label elements

Hazard statements: * H315: Causes skin irritation. H319: Causes serious eye irritation.**Signal word:** Warning**Hazard pictograms:** GHS07: Exclamation mark**Precautionary statement:** P102: Keep out of reach of children.

P264: Wash skin thoroughly after handling.

P280: Wear protective gloves.

P302+352: IF ON SKIN: Wash with plenty of water/soap.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P337+313: If eye irritation persists: Get medical advice/attention.

2.3 Other hazards

Other hazards: Not applicable.**PBT:** This product is not identified as a PBT/vPvB substance

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients:

VINYL TOLUENE - REACH registered number(s): 01-21196222074-50-0000

EINECS	CAS	PBT / WEL	CLP Classification	Percentage
246-562-2	25013-15-4	-	Acute Tox. 4:H332; Asp. tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315	10-20%

SECTION 4: First aid measures

4.1 Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.**Eye contact:** Bathe the eye with running water for 15 minutes.



Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

Ingestion: Wash out mouth with water.

Inhalation: No symptoms.

4.2 Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / Immediate effects: Not applicable.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media for the surrounding fire should be used.

5.2 Special hazards arising from the substance or mixture

Not applicable

5.3 Advice for firefighters:

Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1 Personal precautions:

Refer to section 8 of SDS for personal protection details.

6.2 Environmental precautions:

Do not discharge into drains or rivers.





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

6.3 Methods and material for containment and cleaning up:

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4 Reference to other sections:

Refer to section 13 of SDS.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Handling requirements: Avoid direct contact with the substance.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions: Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3 Specific end use(s):

Building and construction work (SU19).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values: No data available.

8.2 Exposure controls

Engineering measures: Not applicable

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety goggles.

Skin protection: Protective clothing.

Environmental: No special requirement.





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

State: Paste

Colour: (a) White (b) Natural Pine

Odour: Barely perceptible odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Relative density: 1.05

9.2 Other information:

Not applicable.

SECTION 10: Stability and reactivity

10.1 Reactivity:

Stable under recommended transport and storage conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

Not applicable.

10.4 Conditions to avoid:

Air.

10.5 Incompatible materials:

Not applicable..





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

10.6 Hazardous decomposition products:

None if stored and handled correctly.

SECTION 11: Toxicological information

11.1. Information on toxicological effects:

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated

Symptoms / routes of exposure:

Skin contact: There may be mild irritation at site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur.

Inhalation: No symptoms.

Delayed / Immediate effects: Not applicable.

Other information: Not applicable.

Section 12: Ecological information

12.1 Toxicity

Ecotoxicity values: No data available.

12.2 Persistence and degradability:

No data available.

12.3 Bioaccumulative potential:

No bioaccumulative potential.

12.4 Mobility in soil:

Readily absorbed into soil.





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

12.5 Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6 Other adverse effects:

Negligible ecotoxicity.

Section 13: Disposal considerations:

13.1 Waste treatment methods

Disposal operations: Small quantities of the product can be mixed and allowed to cure, then can be disposed as solid waste.

Waste code number: 03 03 99

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

SECTION 16: Other information

Other information:

This safety data sheet is prepared in accordance with Commission Regulation (EU) No. 453/2010

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3:

H226: Flammable liquid and vapour

H304: May be fatal if swallowed and enters airways.





Ultimate Wood Filler

2 Part Styrene Free Wood Filler

2-PART
Styrene Free

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

[Final Page]

