



HB42[®] Ultimate LXP Foam

25/08/2023 - Vs.1

SAFETY DATA SHEET HB42 Ultimate LXP Foam

Section 1: identification of the mixture and of the company

1.1 Product identifier

Trade name HB42 Ultimate LXP Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against Identified Use(s)

Mixture uses: Polyurethane foam sealant

1.3 Details of the supplier of the safety data sheet

Company name: Hilton Banks Limited, Oldfield Road, Hampton, Middlesex, TW12 2HR, United Kingdom

Telephone: +44 (0)20 8979 8284

Fax: +44 (0)20 8979 8294

E-mail: enquiries@hb42.co.uk



1.4 Emergency telephone number

Emergency Phone No. +44 (0)20 8979 8284

Section 2: hazards identification

2.1 Classification of the substance/mixture

The mixture meets the criteria for classification in accordance with Regulation (EC) No. 1272/2008.

Hazard Pictograms:	 GHS08	 GHS02
Signal words:	Danger	



HB42® Ultimate LXP Foam

Hazard statements	H220 H351 H332 H373** H319 H335 H315 H334 H317	Extremely flammable gas. Suspected of causing cancer. Harmful if inhaled. May cause damage to organs through prolonged or repeated exposure <i>exposure cause the hazard</i> >. Causes serious eye irritation. May cause respiratory irritation. Causes skin irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Precautionary statements	P201 P210 P280 P260 P337+P313 P302+P352 P332+P313 P312 P304+P340 P342+P311 P333+P313 P308+P313 P405 P501	Obtain special instructions before use. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. If skin irritation or rash occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Store locked up.

2.2 Hazards Identification

2.3 other hazards

The mixture does not meet the criteria for PBT or vPvB in accordance with the Annex XIII in the Regulation (EC) No. 1272/2008. Based on current knowledge, the mixture does not include greater than 0,1% the ratio of PBT or vPvB substances.

Section 3: composition of ingredients

3.2 mixtures

General chemical description



HB42[®] Ultimate LXP Foam

Polyurethan Foam

Base substances of preparations:

Declaration of the ingredients according to CLP (EC) No 1272/2008:

CAS No.	EC No.	Concentration	Classification
Diphenylmethane-4,4'-diisocyanate 101-68-8	202-966-0	5 % ≤ C < 25	Canc.2 ;H351 Acute Tox.4*; H332 STOT Rep. Exp.2; H373** Eye Irrit. 2;H319 BHOT Rep. Exp.3; H335 Skin Irrit. 2;H315 Respiratory Sens.1;H334 Skin Sens.1;H317
Propane 74-98-6	200-827-9	-	Flammable Aerosol 1;H220
Butane 106-97-8	203-448-7	-	Flammable Aerosol 1;H220
Dimethyl ether 115-10-6	204-065-8	-	Flammable Aerosol 1;H220

Section 4: first-aid measures

4.1 Description of first aid measures

If exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor. Get medical advice if you feel unwell.

Skin Contact: IF ON SKIN:Wash with plenty of soap and water. Get medical advice if you feel unwell. Take off contaminated clothing and wash before reuse. If skin irritation or rash occurs: Get medical advice.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. If symptoms develop and persist, seek medical advice in case of necessity.

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. If eyelids are bonded closed, do not force eye open. Get medical attention.

Ingestion: Consult with a doctor in case swallowing. Rinse mouth.

4.2 Most important symptoms and effects, both acute and delayed.

Harmful if swallowed. Harmful in contact with skin. Causes serious eye irritation. May cause damage to organs. Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed.

See the Section 8 .



HB42[®] Ultimate LXP Foam

Section 5: Fire-Fighting measures

5.1 Extinguishing Media

Suitable extinguishing media: All common extinguishing agents are suitable. Foam, carbon dioxide, dry powder, water spray

Extinguishing media which must not be used for safety reasons: None known.

5.2 Special Hazards Arising from the Mixture

Isocyanate vapors and other irritating or toxic gases may occur during inflammation. In case of exposure to heat the extremely dangerous combustion products like oxides of carbon and nitrogen may occur.

5.3 Advice for Firefighters

Danger of explosion. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Do not allow to enter surface water or drains.

Section 6: Accidental release measures

6.1 Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel

Use personal protective equipment. Keep children away. Provide ventilation. Keep away from igniting sources. Keep away from naked flame or any incandescent material.

For Emergency Responders

Wear personal protective fireproof clothing.

6.2 Environmental Precautions

Do not empty into drains or water. Disposal of the chemicals must be made according to official regulations.

6.3 Methods and Material for Containment and Cleaning Up

Do not pierce or burn, even after use. Flood with water to complete polymerization and scrape off the floor. Dispose of contaminated material as waste according to Section 13.

6.4 Reference to Other

Sections Any information on personal protection and disposal is given in sections 8 and 13.

Section 7: handling and storage



HB42[®] Ultimate LXP Foam

7.1 Precautions for Safe Handling

Avoid contact with eyes and skin. Avoid breathing vapor and mists. Do not drink, eat and smoke in the working area. Wash hands thoroughly after handling, Use nitrile gloves and protective glass. during handling. Exposure to vapours of heated MDI can be extremely dangerous do not enter closed.

areas where isocyanate vapours may gather.

7.2 Conditions for Safe Storage, Including Any Incompatibilities

Keep in a cool, well-ventilated area in original container. Away from heat, sparks and open flame. Keep containers closed safely and check periodically in case leakage and spilling. Protect containers from physical damage.

Carbon dioxide will occur with the moisture contact and this leads pressure increase inside the can.

Keep only in the original container.

7.3 Specific end use(s)

Adhesive.

Section 8: exposure controls/personal protection

8.1 control parameters

According to EH 40/2009 WELs :

EC No.	CAS No.	Component	TWA	STEL
202-966-0	9016-87-9	Difenilmetan-4,4'-diizosiyanat	0,02 mg/m ³	0,07 mg/m ³
200-827-9	74-98-6	Propane	1000 ppm	-
203-448-7	106-97-8	Bütane	600 ppm	750 ppm
204-065-8	115-10-6	Dimethylether	400 ppm	500 ppm

8.2 Exposure controls

Appropriate Engineering Controls:

Ensure good ventilation. Apply all common precautions while working with chemicals. Use explosion-proof electrical/ventilating/lighting equipment. Keep away from heat sparks/open flames/hot surfaces.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P. This recommendation should be matched to local conditions.



HB42[®] Ultimate LXP Foam

Hand protection:

Wear refractive gloves while working with the hot melt.

Eye protection:

Wear protective goggles.

Skin protection:

Wear protective equipment.

Section 9: physical and chemical properties

9.1 Information on Basic Physical and Chemical Properties

Appearance	: Aerosol, Liquid
Color	: Pale yellow
Odor	: Characteristic
pH	: Not Applicable
Melting/ Freezing Point	: Not Applicable
Initial Boiling Point	: Not Applicable
Boiling Range	: Not Applicable
Flash Point	: Closed/ Pressured Vessel 0°C
Evaporation Rate	: Not Applicable
Flammability of Solids and Gases	: Highly flammable
Explosive Limit	: Not Applicable
Vapour Density	: Not Applicable
Vapour Pressure	: Not Applicable
Density 25°C	: 22,00 ±3 kg/m ³
Solubility	: Insoluble in water, reacts with water.
Partition Coefficient (n-octanol/water)	: Not Applicable
Auto-ignition temperature	: Not Applicable
Decomposition Temperature	: Not Applicable
Viscosity	: Not Applicable
Explosive Properties	: Not Applicable
Oxidizing Properties	: Not Applicable

Section 10: stability and reactivity

10.1 Reactivity



HB42[®] Ultimate LXP Foam

May polymerized when heated.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

See section reactivity.

10.4 Conditions to avoid.

Keep away from sunlight and do not expose temperatures above 50°C. Protect containers from physical damage. Keep away from heat, flame and spark. Do not pierce or burn, even after use.

10.5 Incompatible materials

Carbon dioxide will occur with the moisture contact and this leads pressure increase inside the can. Strongly reacts with active hydrogen and water containing materials.

10.6 Hazardous decomposition products

Isocyanate vapours and other irritating or toxic gases may occur during inflammation. In case of exposure to heat the extremely dangerous combustion products like oxides of carbon and nitrogen may occur.

Section 11: toxicological information

11.1 Information of Toxicological Effects

Based on available data, the classification criteria are indicated below:

Sensitization:

An allergic reaction cannot be excluded after repeated skin contact.

Corrosion/Irritation:

Inhalation: May cause respiratory tract irritation. Exposure to vapours above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.



HB42® Ultimate LXP Foam

Skin Contact: Remove the foam contaminated skin with a clean, dry tissue and clean up with a soft solvent and water, respectively. Use moisturizer in case of irritation.

Eye Contact: Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Consult with a doctor in case swallowing General Toxicology Information

General toxicology information:

EC No.	CAS No.	Component	Limiting Values
202-966-0	9016-87-9	Diphenylmethane -4,4'-diisocyanate	0,02 mg/m ³ ; TWA 0,07 mg/m ³ ; STEL
200-827-9	74-98-6	Propane	1000 ppm; TWA
203-448-7	106-97-8	Butane	600 ppm; TWA 750 ppm; STEL
204-065-8	115-10-6	Dimethyl ether	400 ppm; TWA 500 ppm; STEL

Acute Toxicology:

EC No.	CAS No.	Component	Toxicity
202-966-0	9016-87-9	Diphenylmethane -4,4'-diisocyanate	LC50 (rat) : 490mg/m ³ (solunum)
200-827-9	74-98-6	Propane	LC50 (rat) : 658mg/L (solunum)
203-448-7	106-97-8	Butane	LC50 (rat) : 658mg/L (solunum)
204-065-8	115-10-6	Dimethyl ether	LC50 (rat) : 658mg/L (solunum)

Section 12: ecological information

General Ecological Information:

The material is not biodegradable so, do not allow spreading soil, waterways, or wastewater canal.

12.1. Toxicity

EC No.	CAS No.	Component	Toxicity
202-966-0	9016-87-9	Difenilmetan-4,4'- diizosiyanat	LC50 (rat) : 490mg/m ³ (solunum)
200-827-9	74-98-6	Propan	LC50 (rat) : 658mg/L (solunum)
203-448-7	106-97-8	Bütan	LC50 (rat) : 658mg/L (solunum)
204-065-8	115-10-6	Dimetil eter	LC50 (rat) : 658mg/L (solunum)



HB42® Ultimate LXP Foam

12.2. persistence and biodegradability

EC No.	CAS No.	Component	Biodegradable
202-966-0	9016-87-9	Difenilmetan-4,4'-diizosiyanat	Not biodegradable
200-827-9	74-98-6	Propan	Not biodegradable
203-448-7	106-97-8	Bütan	Not biodegradable
204-065-8	115-10-6	Dimetil eter	Not biodegradable

12.3. Bio accumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Based on current knowledge, the mixture does not include greater than 0,1% the ratio of PBT or vPvB substances.

12.6. Other adverse effects

No data available.

Section 13: disposable considerations

13.1 waste treatment methods

If it is possible, try to reuse the mixture. In consultation with the responsible local authority, must be subjected to special treatment. Disposal of the products must be made according to official regulations.

Waste code

According to the directive 2008/98/EC on waste management and the local regulation (02.04.2015 dated- No.29314) the waste code is:

Adhesive: 08 04 09: waste adhesives and sealants containing organic solvents or other dangerous

Package: 16 05 04: gases in pressure containers (including halons) containing dangerous Substances

Section 14: transport information



HB42® Ultimate LXP Foam

14.1. UN Number

ADR/RID, IMDG, ICA/IATA : UN 1950

14.2. UN Proper Shipping Name

ADR/RID, IMDG, ICA/IATA : AEROSOL, yanıcı

14.3. Transport Hazard Class(es)

ADR/RID, IMDG, ICA/IATA : 2.1

14.4. Packaging Group

ADR/RID, IMDG, ICA/IATA : 2

14.5. Environmental Hazards

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

14.6. Special Precautions For User

Avoid high temperature.

14.7. Transport In Bulk According to Annex II of Marpol and The IBC Code

Not applicable.

Section 15: regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

According to EC directive on health and safety precautions while working with chemicals (2009/161/EU) and Directive on Carcinogens or mutagens at work (2004/37/EC) there are no limitations on the products and materials.

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.



HB42[®] Ultimate LXP Foam

The information supplied herein is accurate to the best of our knowledge. Since conditions and methods are beyond our control, no warranty is expressed or implied. You are advised to assess the suitability of the product on a test area before application.

Date of issue: 25th January 2019

HB42

74 Oldfield Road

Hampton

Middx

TW12 2HR

UK

Tel: +44 (0)20 8979 8284

Fax: +44 (0)20 8979 8294

www.hb42.co.uk

sales@hb42.co.uk